



EncapSulite
INTERNATIONAL

Part Number:

S25385

Lamp Description:

F84T12/D/HO

General Description:

ProGuard – Polycarbonate coated: 100W,
84" MOL T12 HO Rapid Start Fluorescent
Lamp, 6500K Color Temp, Daylight,
Phosphor, 76 CRI.

Product Specifications

| | |
|-------------------------------------|-------------------------|
| Lamp Manufacturer: | Sylvania |
| Case Quantity: | 15 |
| Lamp Description: | F84T12/D/HO |
| Actual Length (in): | 81.909 |
| Actual Length (mm): | 2080.49 |
| Average Rated Life (hrs): | 12,000 |
| Base: | Recessed Double Contact |
| Bulb: | T12 |
| High Output: | Yes |
| Color Rendering Index (CRI): | 76 |
| Color Temp/CCT (Kelvins): | 6500 |
| Diameter (in): | 1.593 |
| Diameter (mm): | 40.46 |
| Initial Lumens (25C): | 6700 |
| Mean Lumens (25C): | 5427 |
| Initial Lumens (35C): | N/A |
| Mean Lumens (35C): | 5427 |
| Nominal Length (in): | 84.000 |
| Nominal Length (mm): | 2133.60 |
| Nominal Voltage (V): | N/A |
| Nominal Wattage (W): | 100.00 |
| Coating Name: | ProGuard |
| Coating Material: | Polycarbonate |
| Use in Open Fixture: | Yes |
| Use in Closed Fixture: | No |
| Max Ambient Temperature (F): | 135°F |
| Warranty: | Limited 1-Year |