



EncapSulite
INTERNATIONAL

Part Number: WGP74LED-Amber-T

Fixture Description: TurtleLite-Amber 4 foot LED 70 Series
Waterproof fixture

General Description: UL 1598 Wet Location, UL 8750 LED & UL-EPH.
NOT INTENDED FOR PERMANENT IMMERSION. IP67 Rated



Product Specifications

Fixture Name:	WGP74LED-Amber-T
LED Board Used:	PrevaLED 5000K 9W 255mA (73577)
Average Rated Life (hrs):	50,000
Filter Color	Amber
Fixture Length (in):	48.82
Fixture Length (mm):	1240
Fixture Diameter (in):	2.75
Fixture Diameter (mm):	69.85
Multi-Voltage:	Yes
Voltage (V):	120V, 240V, and 277V
Hardwire:	Yes
Ambient Temperature Range(F):	-40° - 110°
Driver Type:	Sylvania OT30 350-1050mA programmable
Output Wattage:	25W Total
UL-EPH Listed:	UL-EPH
UL Listing:	UL 1598 / UL8750
Wet Locations:	Yes
Indoor/Outdoor Use:	Yes
High-Pressure Hose Down:	1200 PSI
Tube Material:	Xylex 8300
FEP Coated Tube (Upon Request):	Yes
Warranty:	Limited 3-Years