



**EncapSulite**  
INTERNATIONAL

**Part Number:**

WGP102LED-HO-32W

**Fixture Description:**

2 foot 32W LED, 5000 Kelvin, 100 Series  
Diffused White, Waterproof fixture

**General Description:**

NOT INTENDED FOR PERMANENT  
IMMERSION. IP67 Rated



## Product Specifications

<b>Fixture Name:</b>	WGP102LED-HO-32W
<b>LED Board Used:</b>	Fortimo 2Ft 5000K 39.9W 1400mA 6000 LM
<b>Lumens Per Watt:</b>	125
<b>Average Rated Life (hrs):</b>	50,000
<b>Output Wattage:</b>	32W
<b>Nominal Lumens:</b>	4000
<b>Foot Candles 3ft:</b>	--
<b>Foot Candles 4ft:</b>	--
<b>Color Temp/CCT (Kelvin):</b>	5000K
<b>LED CRI:</b>	>80
<b>Nominal Fixture Length (in):</b>	24
<b>Nominal Fixture Length (mm):</b>	610
<b>Actual Fixture Length (in):</b>	25.4375
<b>Actual Fixture Length (mm):</b>	646.1125
<b>Fixture Diameter (in):</b>	4
<b>Fixture Diameter (mm):</b>	100
<b>Multi-Voltage:</b>	Yes
<b>Voltage (V):</b>	120V, 240V, and 277V
<b>Hardwire:</b>	Yes
<b>Ambient Temperature Range(F):</b>	-40° - 110°
<b>Driver Type:</b>	Philips Xitanium SimpleSet 40W
<b>Wet Locations:</b>	Yes
<b>Indoor/Outdoor Use:</b>	Yes
<b>High-Pressure Hose Down:</b>	1200 PSI
<b>Tube Material:</b>	Polycarbonate w/ UV Inhibitors
<b>FEP Coated Tube (Upon Request):</b>	Yes
<b>Diffused Tube</b>	No
<b>Mounting Options:</b>	SS Strap or SS Flush Mount
<b>DLC Certification:</b>	Pending
<b>UL Listing:</b>	UL1598/UL8750/EPH/USL/CSL